you use -@swiftonsecurity

Cryptography is nightmare magic math that cares what kind of pen



Finish Up Software Security & Crypto 1





Announcements & Reminders

Computer Science 161 Fall 2020

• Reminders on the chat....

- Use Q&A to ask questions
- Use chat to talk amongst yourselves: be sure to send to ALL not just "send to panelists"
- Just say SOMETHING, SOMETIME in chat for attendance tracking
- During the short break...
 - Those who still want partners, lets use the chat to find them
- Homework 1 due tomorrow at 11:59 PM PDT
 - No late homework accepted, but you do get one homework drop





Why does software have vulnerabilities?

Computer Science 161

- Programmers are humans. And humans make mistakes.
 - Use tools
- Programmers often aren't security-aware.
 - Learn about common types of security flaws.
- Programming languages aren't designed well for security.
 - Use better languages (Java, Pythor





Testing for Software Security Issues

Computer Science 161 Fall 2020

What makes testing a program for security problems difficult?

- We need to test for the absence of something
 - Security is a *negative* property!
 - "nothing bad happens, even in really unusual circumstances" •
- Normal inputs rarely stress security-vulnerable code
- How can we test more thoroughly?
 - Random inputs (fuzz testing)
 - Mutation
 - Spec-driven
 - Use tools like Valgrind
 - Test corner cases
- How do we tell when we've found a problem?
 - Crash or other deviant behavior
- How do we tell that we've tested enough?
 - Hard: but code-coverage tools can help

Laura (X-23): **Disney's** BEST **Princess!**



Working Towards Secure Systems

- Along with securing individual components, we need to keep them up to date ...
- What's hard about patching?
 - Can require restarting production systems
 - Can break crucial functionality







by Jim Clausing (Version: 2)

2 comment(s)

First off, a huge thank you to readers Ken and Paul for pointing out that Oracle has released Java 7u13. As the CPU (Critical Patch Update) bulletin points out, the release was originally scheduled for 19 Feb, but was moved up due to the active exploitation of one of the critical vulnerabilities in the wild. Their Risk Matrix lists 50 CVEs, 49 of which can be remotely exploitable without authentication. As Rob discussed in his diary 2 weeks ago, now is a great opportunity to determine if you really need Java installed (if not, remove it) and, if you do, take additional steps to protect the systems that do still require it. I haven't seen jusched pull this one down on my personal laptop yet, but if you have Java installed you might want to do this one manually right away. On a side note, we've had reports of folks who installed Java 7u11 and had it silently (and unexpectedly) remove Java 6 from the system thus breaking some legacy applications, so that is something else you might want to be on the lookout for if you do apply this update.

	Storm Cent	er Tools I
arlv		
F Recommend	 veet 🔿 +1	i #





Working Towards Secure Systems

- Along with securing individual components, we need to keep them up to date ...
- What's hard about patching?
 - Can require restarting production systems
 - Can break crucial functionality
 - Management burden:
 - It never stops (the "patch treadmill") ...





News

Computer Science 161 Fall 2020

IT administrators give thanks for light Patch Tuesday

07 November 2011

Microsoft is giving IT administrators a break for Thanksgiving, with only four security bulletins for this month's Patch Tuesday.

Only one of the bulletins is rated critical by Microsoft, which addresses a flaw that could result in remote code execution attacks for the newer operating systems – Windows Vista, Windows 7, and Windows 2008 Server R2.

The critical bulletin has an exploitability rating of 3, suggesting

info security

STRATEGY /// INSIGHT /// TECHNIQUE





Working Towards Secure Systems

Computer Science 161 Fall 2020

- to date ...
- What's hard about patching?
 - Can require restarting production systems
 - Can break crucial functionality
 - Management burden:
 - It never stops (the "patch treadmill") ...
 - ... and can be difficult to track just what's needed where
- Other (complementary) approaches?
 - Vulnerability scanning: probe your systems/networks for known flaws
 - Penetration testing ("pen-testing"): pay someone to break into your systems ...
 - ... provided they take excellent notes about how they did it!

Along with securing individual components, we need to keep them up







RISK ASSESSMENT / SECURITY & HACKTIVISM

Extremely critical Ruby on Rails bug threatens more than 200,000 sites

Servers that run the framework are by default vulnerable to remote code attacks.

by Dan Goodin - Jan 8 2013, 4:35pm PST

Hundreds of thousands of websites are potentially at risk following the discovery of an extremely critical vulnerability in the Ruby on Rails framework that gives remote attackers the ability to execute malicious code on the underlying servers.

The bug is present in Rails versions spanning the past six years and in default configurations gives hackers a simple and reliable way to pilfer database contents, run system commands, and cause websites to crash, according to Ben Murphy, one of the developers who has confirmed the vulnerability. As of last week, the framework was used by more than 240,000 websites, including Github, Hulu, and Basecamp, underscoring the seriousness of the threat.

"It is quite bad," Murphy told Ars. "An attack can send a request to any Ruby on Rails sever and then execute arbitrary commands. Even though it's complex, it's reliable, so it will work 100 percent of the time."

Murphy said the bug leaves open the possibility of attacks that cause one site running rails to seek out and infect others, creating a worm that infects large swaths of the Internet. Developers with the Metasploit framework for hackers and penetration testers are in the process of creating a module that can scan the Internet for vulnerable sites and exploit the bug, said HD Moore, the CSO of Rapid7 and chief architect of Metasploit.

Maintainers of the Rails framework are urging users to update their systems as soon as possible to

Computer Science 161 Fall 2020



HARDENING 38



Some Approaches for Building Secure Software/Systems: Use Mitigations!

Computer Science 161 Fall 2020

Run-time checks

- Automatic bounds-checking (overhead)
- What do you do if check fails? Probably controlled crash...
- Address randomization
 - Make it hard for attacker to determine layout
 - But they might get lucky / sneaky

Non-executable stack, heap

- May break legacy code
- See also Return-Oriented Programming (ROP)

Monitor code for run-time misbehavior

- E.g., illegal calling sequences
- But again: what do you if detected?







Approaches for Secure Software, con't

Computer Science 161

Program in checks / "defensive programming" E.g., check for null pointer even though sure pointer will be valid

- Relies on programmer discipline
- Use safe libraries
 - E.g. strlcpy, not strcpy; snprintf, not sprintf
 - Relies on discipline or tools ...
- Bug-finding tools
 - Excellent resource as long as not many false positives
- Code review
 - Can be very effective ... but expensive





Approaches for Secure Software, con't

Computer Science 161 Fall 2020

• Use a safe language

- E.g., Java, Python, C#, Go, Rust
- Safe = memory safety, strong typing, hardened libraries Installed base? Programmer base? Legacy? Performance?
- Structure user input
 - Constrain how untrusted sources can interact with the system Really key later when we get to SQL injection...
 - Perhaps by implementing a reference monitor
- Contain potential damage
 - E.g., run system components in jails or VMs
 - Think about privilege separation



14

Real World Security: Securing your cellphone... Look on the back:

Computer Science 161 Fall 2020

- Does it say "iPhone"?
 - Keep it up to date and be happy
- Does it say "Pixel"?
 - Keep it up to date and be happy
- Does it say anything else?
 - Toss it in the trash and buy an iPhone SE or a Pixel 4a
- Why? The Android Patch Model...
 - "Imagine if your Windows update needed to be approved by Intel, Dell, and Comcast... And none of them cared or had a reason to care"
 - (Note: Google stopped updating the public dashboard that provided the great pie-chart, which is why this is a 2019 version in the pie chart)

	Android	Platform/	API	Version	Distribution
-					

ANDROID PLATFORM	API LEVEL	CUMULATIVE	Ice Cream
VERSION		DISTRIBUTION	Contacts P
4.0 Ice Cream Sandwich	15		Social APIs User profile
4.1 Jelly Bean	16	99.8%	Invite intent Large photo
4.2 Jelly Bean	17	99.2%	Calendar P
4.3 Jelly Bean	18	98.4%	Voicemail I
4.4 KitKat	19	98.1%	Add voicem Multimedia
5.0 Lollipop	21	94.1%	Media effec and videos
5.1 Lollipop	22	92.3%	Improved n
6.0 Marshmallow	23	84.9%	Face detecti
7.0 Nougat	24	73.7%	Continuous Camera bro
7.1 Nougat	25	66.2%	Connectivit Android Bea
8.0 Oreo	26	60.8%	push with N Wi-Fi P2P co Bluetooth b
8.1 Oreo	27	53.5%	Network us
		39.5%	
9.0 Pie	28		
10. Android 10	29	8.2%	https://deve

engine support

nproved action ba Grid lavout Texture view witch widge

e and contr

Device policies

Device Sensors

Weaver

- roved text-to-speed

- Spell checker service
- nproved popup menu
- Controls for system UI visibil

- Certificate managemen

OK

A Real World Exploitation Example: Exploit on Safari

Computer Science 161 Fall 2020

- This was discovered about 2 year ago: https://blog.ret2.io/2018/07/11/pwn2own-2018-jsc-exploit/
 - But the theme of how this work is quite common: target arrays
- Basic idea: a race condition can enable use-after-free in the JavaScript interpreter
 - And the attacker's code is in JavaScript running on the target browser
- Use to create limited read/write primitive...
- To create arbitrary read/write primitive...
- To create binary code execution!

Any use-after-free in Javascript where you can do this to an arbitrary object will usually





Key Insight #1: JavaScript Arrays...

Computer Science 161 Fall 2020

- JavaScript arrays are length-ch •
 - So you can't read past the end of the ar
- But if we allocate a bunch of ar
 - And they are all still being used...
 - But the runtime has a use-after-free error that allows us to reuse the memory as something else...
 - We can overwrite the length field in the array specifier!
 - create the use-after-free condition)

This gets a relative read/write primitive

JavaScript objects

ecked		
CONCO	JavaScript Array	JavaScript Integer
ray	Length	Value
ravs	Data	
	Data	

Try this a whole bunch of times until successful (since it is probably a race condition to

We have a JavaScript array that can read/write a long hunk of memory including other





Key Insight #2: JavaScript TypedArray objects

Computer Science 161 Fall 2020

- A way for JavaScript to have high performance access to other parts of memory
 - Used for video, audio, etc...
 - Consists of a pointer to non-JavaScript memory and a length field
- JavaScript objects...
 - Now we can both adjust the pointer and the length
- Now we can arbitrarily write & read memory using JavaScript!

JavaScript TypedArray Length Pointer to elsewhere

Runtime can say "Here, JavaScript, this is a fixed blob of memory for you to play with"

So once we can read/write to a hunk of memory containing other

• Lets take one of those objects and rewrite it so the runtime thinks it is a TypedArray object:







Key Insight #3: Why is JavaScript not glacially slow?

- Because JavaScript code is dynamically compiled into machine code!
 - So there exist pages in memory for this code...
 - That are set as both writeable and executable!
- So just find one of them...
 - Create & run JavaScript functions, follow the pointers, and there you go!
- Now we can write assembly... Start it running... And we've won! Full arbitrary code execution!





Of course... Now you have to exit the sandbox!

Computer Science 161 Fall 2020

- sandbox/
- process
 - With a white-list of external resources its now allowed to access
- - has a wide attack surface

https://blog.ret2.io/2018/07/25/pwn2own-2018-safari-

The Safari renderer is running in its own limited-authority

So find a vulnerability in one of those external resources

Which in the Mac case is the "window server" that handles the drawing and







Cryptography: Philosophy...

- This part of the class is really don't try this at home
 - It is *incredibly easy* to screw this stuff up
- It isn't just a matter of making encryption algorithms...
 - Unless your name is David Wagner or Ralcua Popa, your crypto is broken!
- It isn't just a matter of coding good algorithms... Although just writing 100% correct code normally is hard enough!
- There is all sorts of deep voodoo that, when you screw up your security breaks • EG, bad random number generators, side channel attacks, reusing one-use-only items, replay attacks,
 - downgrade attacks, you name it...





LET ME REITERATE!!! DON'T DO THIS AT HOME!!!!

Computer Science 161 Fall 2020

- This summer, 61A did a custom exam tool
 - It would encrypt several python files for each student
 - Every student got a different exam
 - Written by a student who took CS161 already!!! With Me! WITH THESE WARNINGS!!!!
 - Yet I failed... •

Each exam question was supposed to take 20 minutes

- So they would release the key for "question 1" to everyone... Then question 2...
- Everyone had the same key but a different question
- They used a "secure" algorithm... In an insecure way!
 - Breaking this will be a late-semester lab2
- And we don't *know* if it got broken
 - One detected student claimed there was a leakage of the exam before the start





Three main goals

Computer Science

- private data
 - Data = message or document
- Integrity: preventing attackers from altering our data
 - Data itself might or might not be private
- document
 - Generally implies/requires integrity

Confidentiality: preventing adversaries from *reading* our

Authentication: proving who created a given message or







Special guests

Computer Science 161 Fall 2020

Alice

(sender of messages)

• Bob

(receiver of messages)

- The attackers
 - Eve: "eavesdropper"
 - Mallory: "manipulator"











Confidentiality







The Ideal Contest

Computer Science 161

- Attacker's goal: any knowledge of M_i beyond an upper bound on its length
 - Slightly better than 50% probability at guessing a single bit: attacker wins!
 - Any notion of how M_i relates to M_j: attacker wins!
- Defender's goal: ensure attacker has no reason to think any $M' \in \{0,1\}^n$ is more likely than any other
 - (for M_i of length n)







Eve's Capabilities/Foreknowledge

Computer Science 161 Fall 2020

- No knowledge of K
 - We assume **K** is selected by a *truly random process*
 - For **b**-bit key, any $\mathbf{K} \in \{0,1\}^{b}$ is equally likely
- and fully recovered Mi
 - correctly identified a particular bit in M_i
 - There are some attacks where Eve can guess and verify: • Often a side-channel using a "decryption oracle": fooling the server into trying & failing with the nature of different failures telling Eve whether she guessed right
 - Does not apply to scenarios where Eve exhaustively examines every possible $M_i' \in$ **{0,1}**ⁿ

Recognition of success: Eve can generally tell if she has correctly

• But: Eve cannot recognize anything about *partial solutions*, such as whether she has





Eve's Available Information

Computer Science 161 Fall 2020

1.Ciphertext-only attack:

- Eve gets to see every instance of C_i
- Variant: Eve may also have partial information about M_i
 - "It's probably English text"
 - Bob is Alice's stockbroker, so it's either "Buy!" or "Sell"

2.Known plaintext:

- Eve knows part of M_i and/or entire other M_i s
- How could this happen?
 - Encrypted HTTP request: starts with "GET"

 - Eve sees earlier message she knows Alice will send to Bob Alice transmits in the clear and then resends encrypted Alex the Nazi always transmits the weather report at the same time of day, with the word "Wetter" in a known position





Eve's Available Information, con't

Computer Science 161 Fall 2020

3.Chosen plaintext

- Eve gets Alice to send **M**_j's of Eve's choosing
- How can this happen?

4.Chosen ciphertext:

- Eve tricks Bob into decrypting some C_j' of her choice and he reveals something about the result
- How could this happen? •
 - E.g. repeatedly send ciphertext to a web server that will send back different-sized messages depending on whether ciphertext decrypts into something well-formatted Or: measure how long it takes Bob to decrypt & validate

E.g. Eve sends Alice an email spoofed from Alice's boss saying "Please securely forward this to Bob" E.g. Eve has some JavaScript running in Alice's web browser that is contacting Bob's TLS web server







Eve's Available Information, con't

Computer Science

5.Combinations of the above

- Ideally, we'd like to defend against this last, the most powerful attacker
- discussing different considerations

And: we can!, so we'll mainly focus on this attacker when





Independence Under Chosen Plaintext Attack game: IND-CPA

- Eve is interacting with an encryption "Oracle"
 - Oracle has an unknown random key k •
- Eve can provide two separate chosen plaintexts of the same length
 - Oracle will randomly select one to encrypt with the unknown key
 - The game can repeat, with the oracle using the same key...
- Goal of Eve is to have a better than random chance of guessing which plaintext the oracle selected
 - Variations involve the Oracle always selecting either the first or the second record







Designing Ciphers

Computer Science 161 Fall 2020

- Clearly, the whole trick is in the design of E(M,K) and D(C,K)
- One very simple approach: E(M,K) = ROTK(M); D(C,K) = ROT-K(C)through the alphabet
- E.g., $M_i = "DOG"$, K = 3 $C_i = E(M_i, K) = ROT3("DOG") = "GRJ"$ $D(C_i,K) = ROT-3("GRJ") = "DOG"$
- "Caesar cipher"
 - "This message has been encrypted twice by ROT-13 for your protection"

i.e., take each letter in M and "rotate" it K positions (with wrap-around)









Computer Science 161 Fall 2020

Brute force: try every possible value of K

- Work involved?
- At most 26 "steps"





Computer Science 161 Fall 2020

Brute force: try every possible value of K

- Work involved?
- At most 26 "steps"
- Deduction:
 - Analyze letter frequencies ("ETAOIN SHRDLU")
 - Known plaintext / guess possible words & confirm

• E.g. "JCKN ECGUCT" =?

N SHRDLU") words & confirm





Computer Science 161 Fall 2020

Brute force: try every possible value of K

- Work involved?
- At most 26 "steps"
- Deduction:
 - Analyze letter frequencies ("ETAOIN SHRDLU")
 - Known plaintext / guess possible words & confirm

E.g. "JCKN ECGUCT" =? "HAIL CAESAR"

N SHRDLU") words & confirm SAR"





- Brute force: try every possible value of K
 - Work involved?
 - At most 26 "steps"
- Deduction:
 - Analyze letter frequencies ("ETAOIN SHRDLU")
 - Known plaintext / guess possible words & confirm
 - E.g. "JCKN ECGUCT" =? "HAIL CAESAR" \Rightarrow K=2
 - Chosen plaintext
 - E.g. Have your spy ensure that the general will send "ALL QUIET", observe "YJJ OSGCR" \Rightarrow K=24
- Is this IND-CPA?





Break Time!

Computer Science 161 Fall 2020

Hey, lets use chat to find partners!





Kerckhoffs' Principle

Computer Science 161

- knows all internal details
 - Don't rely on security-by-obscurity
- Key should be only thing that must stay secret
- It should be easy to change keys
 - Actually distributing these keys is hard, but we will talk about that particular problem later.
 - But key distribution is one of the real...

Cryptosystems should remain secure even when attacker





Better Versions of Rot-K?

Computer Science 161 Fall 2020

- Consider $E(M,K) = Rot \{K_1, K_2, ..., K_n\}(M)$
 - over with \mathbf{K}_1, \ldots
 - $K = \{ K_1, K_2, ..., K_n \}$
- How well do previous attacks work now?
 - Brute force: key space is factor of 26⁽ⁿ⁻¹⁾ larger
 - E.g., $n = 7 \Rightarrow 300$ million times as much work
 - Letter frequencies: need more ciphertext to reason about
 - Known/chosen plaintext: works just fine
- character of ciphertext
 - We just described 2,000 years of cryptography

• i.e., rotate first character by K_1 , second character by K_2 , up through nth character. Then start

Can go further with "chaining", e.g., 2nd rotation depends on K₂ and first







And Cryptanalysis: ULTRA

Computer Science 161 Fall 2020

During WWII, the Germans used *enigma*:

- System was a "rotor machine": A series of rotors, with each rotor permuting the alphabet and every keypress incrementing the settings
 - Key was the selection of rotors, initial settings, and a permutation plugboard
 - A great graphical demonstration: https://observablehq.com/@tmcw/enigma-machine

 The British built a system (the "Bombe") to bruteforce Enigma

- Required a known-plaintext (a "crib") to verify decryption: e.g. the weather report
- Sometimes the brits would deliberately "seed" a naval minefield for a chosen-plaintext attack



One-Time Pad

Computer Science 161 Fall 2020

- Idea #1: use a different key for each message M
 - Different = completely independent
 - So: known plaintext, chosen plaintext, etc., don't help attacker
- Idea #2: make the key as long as M
- $E(M,K) = M \oplus K \quad (\oplus = XOR)$







0

41

One-Time Pad

Computer Science 161

- Idea #1: use a different key for each message M
 - Different = completely independent
 - So: known plaintext, chosen plaintext, etc., don't help attacker
- Idea #2: make the key as long as M
- $E(M,K) = M \oplus K \quad (\oplus = XOR)$ $D(C,K) = C \oplus K$ $= \mathbf{M} \oplus \mathbf{K} \oplus \mathbf{K} = \mathbf{M} \oplus \mathbf{0} = \mathbf{M}$

(+) $X \oplus 0 = X$ $\mathbf{X} \oplus \mathbf{X} = \mathbf{0}$ $X \oplus Y = Y \oplus X$ $X \oplus (Y \oplus Z) = (X \oplus Y) \oplus Z$





0



One-Time Pad: Provably Secure!

Computer Science

- Let's assume Eve has partial information about M
- We want to show: from **C**, she does not gain any further information
- Formalization: supposed Alice sends either M' or M'' Eve doesn't know which; tries to guess based on C
- Proof:
 - For random, independent K, all possible bit-patterns for C are equally likely
 - This holds regardless of whether Alice chose M' or M'', or even if Eve provides M' and **M**^{''} to Alice and Alice selects which one (IND-CPA)
 - Thus, observing a given C does not help Eve narrow down the possibilities in any way:









One-Time Pad: Provably Impractical!

- Problem #1: key generation
 - Need truly random, independent keys
- Problem #2: key distribution
 - Need to share keys as long as all possible communication
 - If we have a secure way to establish such keys, just use that for communication in the first place!
 - Only advantage is you can communicate the key in advance: you may have the secure channel now but won't have it later





Two-Time Pad?

Computer Science 161

- What if we reuse a key K jeeeest once?
- Alice sends C = E(M, K) and C' = E(M', K)
- Eve observes M

 K and M'

 K
 - Can she learn anything about M and/or M' ?
- Eve computes $\mathbf{C} \oplus \mathbf{C'} = (\mathbf{M} \oplus \mathbf{K}) \oplus (\mathbf{M'} \oplus \mathbf{K})$





Two-Time Pad?

- What if we reuse a key K jeeeest once?
- Alice sends C = E(M, K) and C' = E(M', K)
- Eve observes $\mathbf{M} \oplus \mathbf{K}$ and $\mathbf{M'} \oplus \mathbf{K}$
 - Can she learn anything about M and/or M' ?
- Eve computes $\mathbf{C} \oplus \mathbf{C'} = (\mathbf{M} \oplus \mathbf{K}) \oplus (\mathbf{M'} \oplus \mathbf{K})$ = (M ⊕ M') ⊕ (K ⊕ K) = (M ⊕ M') ⊕ 0 $= \mathbf{M} \oplus \mathbf{M}'$
- Now she knows which bits in M match bits in M'
- And if Eve already knew M, now she knows M!
 - Even if not, Eve can guess **M** and ensure that **M'** is consistent





VENONA: Pad Reuse in the Real World

Computer Science 161 Fall 2020

- The Soviets used one-time pads for communication from their spies in the US
 - After all, it is provably secure!
- During WWII, the Soviets started reusing key material
 - Uncertain whether it was just the cost of generating pads or what...
- VENONA was a US cryptanalysis project designed to break these messages
 - Included confirming/identifying the spies targeting the US Manhattan project
 - Project continued until 1980!

Not declassified until 1995!

- So secret even President Truman wasn't informed about it.
- But the Soviets found out about it in 1949, but their one-time pad reuse was fixed after 1948 anyway





Number Stations: One Time Pads in the Real World

- There are shortwave and terrestrial radio "number stations"
 - At a regular time, a voice gets on the air, reads a series of seemingly random numbers
- For those without a corresponding one-time pad...
 - They are simply a sequence of random numbers
- But if you do have the one-time pad...
 - You can decrypt the super-secret spy message being sent to you
- But what if you don't want to send anything to any spies?
 - Just read out a list of random numbers anyway





"Traffic Analysis" & "Sidechannels"

Computer Science 161

- when
 - Can often reveal umm, interesting secrets
- Sidechannels: Something outside the cryptography itself that reveals something interesting
 - How modern crypto systems are usually broken

Traffic analysis: Simply knowing who is talking to whom or





49

A Sidechannel/Traffic Analysis Spy Example

- In the 90s, there were some Russian spies in the US
 - "The Americans" was based on this incident
- A cuban-broadcast numbers station had a bug...
 - Some nights it would never say "9"
- It turned out this corresponded when the Russian spies were on vacation!
 - And the FBI used that as part of their investigation!
- (Revealed inadvertently by Struck and analyzed by Matt Blaze)







Modern Encryption: Block cipher

Computer Science 161 Fall 2020

- bits), we get:
- EK: $\{0,1\}^b \rightarrow \{0,1\}^b$ denoted by $E_K(M) = E(M,K)$.
 - (and also **D(C,K)**, **E(M,K)**'s inverse)
- Three properties:
 - Correctness:
 - $E_{\kappa}(M)$ is a permutation (bijective function) on b-bit strings •
 - Bijective \Rightarrow invertible
 - Efficiency: computable in μ sec's
 - Security:
 - For unknown **K**, "behaves" like a random permutation
- Provides a building block for more extensive encryption

• A function $E : \{0, 1\}^b \times \{0, 1\}^k \rightarrow \{0, 1\}^b$. Once we fix the key K (of size k



51

DES (Data Encryption Standard)

- Designed in late 1970s
- Block size 64 bits, key size 56 bits
- NSA influenced two facets of its design
 - Altered some subtle internal workings in a mysterious way
 - Reduced key size 64 bits \Rightarrow 56 bits
 - Made brute-forcing feasible for attacker with massive (for the time) computational resources
- Remains essentially unbroken 40 years later!
 - The NSA's tweaking hardened it against an attack "invented" a decade later
- However, modern computer speeds make it completely unsafe due to small key size







Today's Go-To Block Cipher: AES (Advanced Encryption Standard)

- >20 years old, standardized >15 years ago...
- Block size 128 bits
- Key can be 128, 192, or 256 bits
 - 128 remains quite safe; sometimes termed "AES-128", paranoids use 256b
- As usual, includes encryptor and (closely-related) decryptor
 - How it works is beyond scope of this class... But if you are curious: http://www.moserware.com/2009/09/stick-figure-guide-to-advanced.html
- Not proven secure
 - But no known flaws
 - The NSA uses it for Top Secret communication with 256b keys: stuff they want to be secure for 40 years including possibly unknown breakthroughs!
 - so we assume it is a secure block cipher





AES is also effectively free...

Computer Science 161 Fall 2020

- Computational load is remarkably low
 - Partially why it won the competition: There were 3 really good finalists from a performance viewpoint: Rijndael (the winner), Twofish, Serpent One OK: RC6 One ugggly: Mars
- On any given computing platform: Rinjdael was *never* the fastest
- But on every computing platform: Rinjdael was *always* the second fastest
 - The other two good ones always had a "this is the compute platform they are bad at"
- And now CPUs include dedicated AES support







54

How Hard Is It To Brute-Force 128-bit Key?

- 2¹²⁸ possibilities well, how many is that?
- Handy approximation: $2^{10} \approx 10^{3}$
- $2^{128} = 2^{10*12.8} \approx (10^3)^{12.8} \leq (10^3)^{13} \approx 10^{39}$





How Hard Is It To Brute-Force 128-bit Key?

- 2¹²⁸ possibilities well, how many is that?
- Handy approximation: $2^{10} \approx 10^{3}$
- $2^{128} = 2^{10*12.8} \approx (10^3)^{12.8} \leq (10^3)^{13} \approx 10^{39}$
- Say we build massive hardware that can try 10⁹ (1 billion) keys in 1 nanosecond (a billionth of a second)
 - So 10¹⁸ keys/sec
 - Thus, we'll need $\approx 10^{21}$ sec
- How long is that?
 - One year $\approx 3 \times 10^7$ sec
 - So need $\approx 3x10^{13}$ years ≈ 30 trillion years







What about a 256b key in a year?

Computer Science 161 Fall 2020

- Time to start thinking in astronomical numbers:
 - If each brute force device is 1mm³...
 - We will need 10⁵² of these things...
- 10⁴³ cubic meters...
- Or the volume of 7x10¹⁵ suns!
- Brute force is *not a factor* against modern block ciphers...
 IF the key is actually random!

ns! against





Issues When Using the Building Block

Computer Science

- If **M** is smaller, easy, just pad it (more later)
- If **M** is larger, can repeatedly apply block cipher
 - Particular method = a "block cipher mode"
 - Tricky to get this right!
- same

Block ciphers can only encrypt messages of a certain size

If same data is encrypted twice, attacker knows it is the

Solution: incorporate a varying, known quantity (IV = "initialization vector")





58

Electronic Code Book (ECB) mode

Computer Science

- Simplest block cipher mode
- Split message into b-bit blocks P₁, P₂, ...
- other blocks $C_i = E(P_i, K)$
- Since key K is fixed, each block is subject to the same permutation
 - designated output)

Each block is enciphered independently, separate from the

(As though we had a "code book" to map each possible input value to its









Electronic Codebook (ECB) mode encryption







Electronic Codebook (ECB) mode decryption

ECB Decryption

Problem: Relationships between P_i's reflected in C_i's





IND-CPA and ECB?

- Of course not!
- M,M' is 2x the block length...
 - $\mathbf{M} = all 0s$
 - M' = 0s for 1 block, 1s for the 2nd block
- This has catastrophic implications in the real world...









Original image, RGB values split into a bunch of b-bit blocks







Encrypted with ECB and interpreting ciphertext directly as RGB







Later (identical) message again encrypted with ECB





Building a Better Cipher Block Mode

Computer Science 161

- Ensure blocks incorporate more than just the plaintext to mask
 - Idea #1: include elements of prior computation
 - Idea #2: include positional information
- Plus: need some initial randomness

 - Introduce initialization vector (IV):
- Example: Cipher Block Chaining (CBC) which we will discuss next time

relationships between blocks. Done carefully, either of these works:

Prevent encryption scheme from determinism revealing relationships between messages

IV is a public *nonce*, a use-once unique value: Easiest way to get one is generate it randomly







