Computer Science 161 Fall 2020



# The Web...



# You should have your final midterm logistics email...

Computer Science 161 Fall 2020

- If not, post on Piazza ASAP!
- exam

# We will shortly have example setups from TAs testing the



# About Project 2... In Soft Release

## Computer Science 161 Fall 2020

## Not only is it to teach you the difficulty of implementing crypto systems

- Real-world cruel grading would be "1 security bug -> 0 credit!"
- This is the "Kobyashi Maru" project: I don't want anybody to get 100%! But I want everyone to get >80%. You learn from failure too, not just success
  - I really don't want you building crypto-systems outside this class! When I've had students go on and do it, they've failed!

## But to also test/teach by doing some important software engineering skills

- Using a safe language (Go)
- Developing good tests
  - Go has an excellent testing infrastructure
- Design *first!*
- Serialization & Deserialization of Data
  - How to go from program internal representations to blobs-of-data and back...



# Don't write code first, design first!

Computer Science 161 Fall 2020

- Read all parts...
- Write your design document *first*
- Good design makes the project easy (ish)
  - My 100% solution for the slightly simpler version last year is <400 LOC...</li>
  - But of course my initial 100% solution actually had a bug!
- Couple more hints on the design...
  - What do HMAC and Argon2 do?
  - When in doubt there is the universal CS solution: add another layer of indirection!

When you ask the TAs for help, they are instructed to start with your design document!



# The Data Storage Problem:

## Computer Science

- You have some ugly internal data structures...
  - It doesn't really matter what it is, but lots of pointers, arrays, and other ugly things...
- You need to convert it to a single string of bits
  - For storage, encryption, transmission, whatever
  - And go the other way, turn it back into the data structure
- This is called serialization and deserialization: Turning your data into a sequence of bits



# Paradigm #1: Do It Manually...

Computer Science 161 Fall 2020

## The C/C++ traditional world

- Also very common in network programming
- Python's struct module as well
- Define a byte order
  - If you need to go between different instruction sets!
- Pack/unpack data into bytes
  - If you may have endianness, use **ntoh** and **hton**
- Generally safe when adversaries hand you data...
  - Assuming you don't do classic memory screwups that is
- Generally a PitA!



# Paradigm #2: Java serialize & python pickle...

## Computer Science 161 Fall 2020

- Nice and convenient:
  - Allows you to dump and restore arbitrary objects
- But horribly dangerous!
  - If an adversary provides an object, it can deserialize to **basically anything they want**!
- Never, ever ever ever use these if you are communicating outside your own program!
  - They are not suitable for a malicious environment!
- input...
  - And then another programmer creates a path where the function is reachable from untrusted input
- So add these to your "search" list for 'you just got handed a new project'
  - Along with system() and direct calls to SQL databases, along with unsafe C string operations: If you see **serialize** or **pickle**: worry if you need to worry about untrusted input!

Common programmer F-up: Use serialize or pickle *thinking* it will only have trusted





# Paradigm #3: Google Protocol Buffers

Computer Science 161 Fall 2020

- Provides a compiler to compile code to pack/unpack structures
  - Highly efficient binary encoding
  - Available for C++, python, java, go, ruby, Objective-C, C#
- to pack/unpack structures
  - And its not human readable in the slightest

# Safe, but requires using an external compiler to create code





# Paradigm #4: XML and JSON

- Text based formats
  - Human readable-ish: Don't underestimate the value in being able to read your computer data directly!
- JSON is small and simple
  - Just a few types in key/value pair structures
- XML is grody and complex...
  - XML parsers tend to have bugs.
- Both are less compact
  - Lots of useless text as they are ASCII format, not binary
- So we provide you with Json marshal/unmarshal!
  - Hint: You can coerce the bytes to a string if you want to print what is being written!



# Personal Preference: When in doubt, use json.

- It is cross platform like Google Protocol Buffers
  - But doesn't require any external compiler support
- It is simple
- It is "geek readable"
  - Especially if you turn on pretty-printing to add newlines
- It is really easy for web applications to use
  - JavaScript directly recognizes it! "JavaScript Object Notation"
- Space overhead pretty much goes away with compression
  - ASCII text is "less efficient" than binary, but gzip() of ASCII text becomes effectively the same in the limit:
    - Compression gets pretty close to the Shannon's limit these days
  - And the web compresses everything pretty much by default





# Web Security: Web History...

Computer Science 161 Fall 2020

- day is so incredibly fsck'ed...
  - And the web, is indeed, strongly fsck'ed up
- We saw that on the back end on Monday...
  - system and SQL were designed for non-secure environments

# Often one needs to start with history to realize why present



# The Prehistory Idea: Memex...

- Observation from 1945: We need a conceptual way to organize data
  - A reference library may have a ton of stuff, but how do you find something?
  - Microfilm is even more compact
  - E.g. a single microfiche card is a 105mm x 148mm piece of film
    - That can hold photos of 100 *pages* of text!
- But how do we find and understand things?
  - Idea from Vannevar Bush: WW2 head of the primary military R&D office
- https://en.wikipedia.org/wiki/Memex





# The Memex...

- A big integrated desk that can store and access microfilm... •
  - The most compact storage available at the time
- Idea #1: "Trails"
  - Rather than just view pages of data linearly...
  - You could follow a "trail": A linear path through an arbitrary sequence of actual film
    - This is what we'd now call a "hyperlink": Refer to another piece of data by location
  - You could also create "personal trails": your own custom path for
- Idea #2: "Upload data"
  - It would also include a photographic hood: You could then add it to the collection in the Memex
- Never actually *built* but conceptually very important
- Note that it was only about accessing data, not code!



# HTML, HTTP, and URLs

Computer Science 161

# • HTML: Hyper Text Markup Language

<A HREF="....">, <IMG SRC="...">)

# HTTP: Hyper Text Transfer Protocol

- A (cleartext) protocol used to fetch HTML and other documents from a remote server (the "Web server")
- URLs: Uniform Resource Locators
  - A text format for identifying where a piece of data is in the world...

A text-based representation with "tags" (e.g. <TITLE>this is a title</TITLE>,



# The URL, which is a URI (Uniform Resource Identifier

**Computer Science 161 Fall 2020** 



- Scheme: What protocol to use, e.g.
  - "ftp" File Transfer Protocol
  - "http" Hyper Text Transfer Protocol
  - "https" Encrypted HTTP
  - "file" A local file on the network
  - "git+ssh" a SSH tunneled git fetch

# https://en.wikipedia.org/wiki/Uniform Resource Identifier

# The URL Continued: Location



- Remote location: "//..."
  - Username followed by @ if there is one (optional)
  - Host, the remote computer (mandatory if remote)
    - Either a hostname or an IP (Internet Protocol) address
  - Remote port (if different from the default, optional)
    - Networking speaks in terms of remote computers and ports
- This is "where to find the remote computer"

# The URL Continued: Path



- Path is mandatory and starts with /
  - "/" alone is the "root" of the directory tree, and must appear
- Directory entries are separated with /
  - Unix style rather than Window's style \
- Sent to the remote computer to tell it where to look for the file starting at its own root directory for data that it is sharing



# The URL Continued: Query



- Query is optional and starts with ?
  - Need to encode ? as %3f if elsewhere in the URI
- This is sent to the remote server
  - Commonly designed as a set of key/value pairs... EG, • Name=Nick&Role=SuperGenius
  - Remote server will then interpret the data appropriately

# The URL Continued: Fragment



- Fragment is optional and starts with #
- This is not sent to the remote server!
  - Only available to the local content
  - Initially intended just to tell the web browser where to jump to in a document...
  - But now used for JavaScript to have local content in the URL that isn't sent over to the server

# URIs are ASCII text

## Computer Science 161 Fall 2020

- - %20 = ' '
  - %35 = '#'
- Can optionally encode normal ASCII characters too!
  - %50 = '2'
- Can make it hard to detect particular problems... •
  - EG, /%46%46/etc/password converts to: /../etc/password
    - Will go "above the root" if the web server is misconfigured to grab the password file!

 It is an ASCII (plain text) format: Only 7 bits with "printable" characters To encode non-printable characters, spaces, special characters (e.g. ?, #, /) you must "URL encode" as %xx with xx being the hexadecimal value





# HTTP (Hypertext Transfer Protocol)

Computer Science 161 Fall 2020

## A common data communication protocol on the web



WEB SERVER

## HTTP REQUEST:

GET /account.html HTTP/1.1

Host: www.safebank.com

## HTTP RESPONSE:

HTTP/1.0 200 OK <HTML> . . . </HTML>





# HTTP

Computer Science 161 Fall 2020



## WEB SERVER

## HTTP REQUEST:

GET /account.html HTTP/1.1 Host: www.safebank.com

## HTTP RESPONSE:

HTTP/1.0 200 OK <html> . . . </html>





# HTTP Request

## Computer Science 161 Fall 2020

**GET:** no side effect (supposedly, HA)

**POST:** possible side effect, includes additional data

**HEAD: only the** first part of the content



## **Data – none for GET**



# HTTP

## Computer Science 161 Fall 2020



## WEB SERVER

## HTTP REQUEST:

GET /account.html HTTP/1.1 Host: www.safebank.com

> HTTP RESPONSE: HTTP/1.0 200 OK

<HTML> . . </HTML>





# HTTP Response





Web page





# HTML

Computer Science 161 Fall 2020

## A language to create structured documents One can embed images, objects, or create interactive forms





# CSS (Cascading Style Sheets)

**Computer Science 161 Fall 2020** 

## Language used for describing the presentation of a document

## index.css

```
p.serif {
font-family: "Tim
}
p.sansserif {
font-family: Aria
}
```

font-family: "Times New Roman", Times, serif;

font-family: Arial, Helvetica, sans-serif;



# Originally There Was Only HTTP...

Computer Science 161 Fall 2020

- It was a way of expressing the text of the documents
  - With other embedded content like images...
- And it was good, but...
- Sun had a programming language called "Java"
- So they created a language called "JavaScript"
  - Only thing in common with "Java" is the name and bits of the syntax

Designed to compile to an intermediate representation and run on a lot of systems

## They built a web browser that could also fetch and execute Java...

• But Java was too powerful: It was designed to do everything a host program could do





# Javascript

Computer Science 161 Fall 2020

## Programming language used to manipulate web pages. It is a high-level, dynamically typed and interpreted language with support for objects. It is why web sites are now programs running in the browser Supported by all web browsers

<script> function myFunction() document.getElementById("demo").innerHTML = "Text changed."; </script>





# Lots Of Work To Make This Fast...

- These days JavaScript is used just about everywhere
  - So a lot of work goes into making this execute quickly
- Common technique: "Just In Time Compiler"
- Initially interprets JavaScript
- After a function is interpreted enough, convert the function into native machine code So need some memory that is both executable AND writeable...
- Which is why vulnerabilities in the JavaScript interpreter/compiler are so dangerous Attacker is already running code, its just "sandboxed" to limit what it can do
- - Gain an arbitrary read/write primitive: EG "use after free" on a JavaScript object
  - Now can have the JavaScript program inspect memory!
  - Breaks ALSR: The attacker's program can examine memory to derandomize things
  - Breaks W^X: Find something in the W&X space to overwrite with the attacker's code...
    - No need to do those silly ROP chains...



# HTTP

Computer Science 161 Fall 2020

## CLIENT BROWSER





## WEB SERVER

## HTTP REQUEST:

GET /account.html HTTP/1.1

Host: www.safebank.com

## **HTTP RESPONSE:**

HTTP/1.1 200 OK <HTML> . . </HTML> webpage





# Page rendering





# DOM (Document Object Model)

**Computer Science 161 Fall 2020** 

## **Cross-platform** model for representing and interacting with objects in HTML

```
HTML
<html>
    <body>
        <div>
            foo
        </div>
        <form>
            <input type="text" />
            <input type="radio" />
            <input type="checkbox" />
        </form>
    </body>
</html>
```





# The power of Javascript

**Computer Science 161 Fall 2020** 

## Get familiarized with it so that you can think of all the attacks one can do with it.





# What can you do with Javascript?

Computer Science 161 Fall 2020

Almost anything you want to the DOM! A JS script embedded on a page can of the page.

The same happens if an attacker manages to get you load a script into your page. w3schools.com has nice interactive tutorials

# modify in almost arbitrary ways the DOM



# Example of what Javascript can do...

**Computer Science 161 Fall 2020** 

## Can change HTML content:

<button type="button"</pre> 'Hello JavaScript!'"> Click Me!</button>

**DEMO** from

- JavaScript can change HTML content.
- onclick="document.getElementById('demo').innerHTML =

## http://www.w3schools.com/js/js\_examples.asp



# Other examples

Computer Science 161 Fall 2020

Can change images Can chance style of elements Can hide elements Can unhide elements Can change cursor...

the DOM

## Basically, can do anything it wants to



# Another example: can access cookies (Access control tokens)

Computer Science 161 Fall 2020

# Read cookie with JS:

var x = document.cookie;

## Change cookie with JS:

document.cookie = "username=John Smith; expires=Thu, 18
Dec 2013 12:00:00 UTC; path=/";



# Frames

**Computer Science 161 Fall 2020** 

## Enable embedding a page within a page <iframe src="URL"></iframe>







# Frames



- Modularity
  - Brings together content from multiple sources
  - Client-side aggregation
- Delegation
  - Frame can draw only inside its own rectangle



# Frames

Computer Science 161 Fall 2020

- Outer page can specify only sizing outer page
- page cannot change contents of outer page

and placement of the frame in the

 Frame isolation: Outer page cannot change contents of inner page; inner



# Desirable security goals

- sites
- our online activities
- from accessing our web resources

**Integrity:** malicious web sites should not be able to tamper with integrity of our computers or our information on other web

 Confidentiality: malicious web sites should not be able to learn confidential information from our computers or other web sites Privacy: malicious web sites should not be able to spy on us or

Availability: malicious parties should not be able to keep us



Weaver

# Security on the web

## Computer Science 161

- files/programs on our computers
  - Browsing to awesomevids.com (or evil.com) should not infect our computers with malware, read or write files on our computers, etc...
  - We generally assume an adversary can cause our browser to go to a web page of the attacker's choosing
- Mitigation strategy
  - Javascript is sandboxed: it is *not allowed* to access files etc...
  - Browser code tries to avoid bugs:
    - Privilege separation, automatic updates
    - Reworking into safe languages (rust)

# Risk #1: we don't want a malicious site to be able to trash



# Security on the web

Computer Science 161

- websites
  - Browsing to evil.com should not let evil.com spy on our emails in Gmail or buy stuff with our Amazon accounts
- Defense: Same Origin Policy
  - An *after the fact* isolation mechanism enforced by the web browser

## Risk #2: we don't want a malicious site to be able to spy on or tamper with our information or interactions with other



# Security on the web

- Risk #3: we want data stored on a web server to be protected from unauthorized access
- Defense: server-side security



# Major Property: "Same Origin Policy"

- Basic idea:
  - A web page runs from an 'origin': A remote domain/protocol/port tuple.
- Within that origin, the web page runs code in the browser
  - But is only supposed to affect things within the same origin
- The web browser *must* enforce this isolation
  - Otherwise, a malicious web site can cause behaviors on other web sites
- Matching is exact
  - http://www.example.com, https://www.example.com, http://example.com are all different origins



# Same Origin Controls What A Page Can Do...

Computer Science 161 Fall 2020

## Can *fetch* images and content *regardless of origin*

- But can *not* determine detailed properties: Images are blank squares when loaded cross-origin
- Remote scripts run within the origin of the page, not the origin where they are fetched from
- Can create frames
  - Each frame can be in its own origin...
- Can only do certain calls (e.g. xml-http-request) to the origin
- Summary here:

# Can only *communicate* with frames from the same origin or with origin crossing options

https://developer.mozilla.org/en-US/docs/Web/Security/Same-origin\_policy





# Can change origin up...

Computer Science 161 Fall 2020

- www.example.com can change its origin to be example.com
- But can't change origin down

But once it does so, it is no longer in the origin of www.example.com



# But Cookies Are Different

## Computer Science

- Cookies can be set by a remote website
  - With the set-cookie: header
- And can also be set by JavaScript
- Common usage: user authentication
  - EG, set a "magic value" to identify the user
  - The server can then check that value on subsequent fetches
- If someone or another web-site can get this cookie...
  - They can impersonate that user
  - Attacker goal is to often get cookies of other web-sites



# Cookie Origin Rules != JavaScript Same Origin

- Cookies are generally described as key/value pairs
  - username=nick
  - authcookie=nSFCOAusrr97097y03
- Cookies are set with an associated hostname/path binding •
  - EG, example.com/foo
- It will be sent to all websites who's suffix fully matches:
  - www.example.com/foo will get it
  - example.com/bar won't get it
- Further complicating things:
  - Although set using name/domain/path/value...
  - They are read (in *unspecified order*) as just name/value
  - There is **no way to know** if you have two copies of the username cookie which one is legit!
  - Leads to fun "Cookie stuffing" attacks
- https://developer.mozilla.org/en-US/docs/Web/HTTP/Cookies



# Secure and http-only

## Computer Science

## Cookies, by default, will be sent over both http and https

- Designed so you can have a "secure" login page but "insecure" main pages...
- From back when the security of HTTPS was considered "expensive"
- Which means that anyone listening in can capture the cookies
  - "Firesheep": A browser plug-in designed to make it easy to steal login cookies

# • "Fix": the "secure" flag

- Cookie will only be sent over encrypted connections
  - But you could set it with an insecure connection (now fixed)

# http-only: Only set in the cookie header

- Not accessible to JavaScript: Designed to protect (a bit) from rogue scripts



# Example of Cookie Failures: Spectre...

- It used to be Chrome isolated different tabs in different Unix processes
  - Both for security sandboxing (you'd need to both exploit the browser AND escape the sandbox to compromise a user) and so if a tab crashed, the browser wouldn't
- Spectre: A hardware sidechannel attack
  - Observation: There are many cases where a program may want to keep data safe from other parts of the same program...
- The big one in this case is JavaScript
  - If you have multiple origins running in the same tab... and one script could read another origin's cookies...
  - It is game over



# Real World Spectre: How It Works

Computer Science 161 Fall 2020

- evil.com gets the user to visit its web page
  - Starts running in a browser tab
- evil.com then opens a frame to victim.com
  - Now under the isolation rules: JavaScript in evil.com must not be able to read any memory from victim.com... In particular the cookies
- - So the only memory protection is enforced by the JavaScript JIT
- Goal: break the isolation, read memory from victim...

But they are running in the same operating system process



# Modern Processors: Insanely Complex Beasts...

Computer Science 161 Fall 2020

- In order to get good IPC (Instructions per cycle), modern processors are insanely aggressive
  - Branch prediction: guess which way a program is going to go and do it Aggressive caches: cache everything possible

  - Speculative execution: uh, think I'm going to need this, do it anyway

## Spectre's key idea

- We can detect the results of failed speculative execution: A side-channel attack such as timing, cache state, etc...
  - Allows us to see what the input to the speculative execution was
- We can *force* speculative execution by making the processor guess wrong
- We can then *read* the side channel to know the results of the execution



# So Spectre-JS

- evil.com loads victim.com in a frame
- And evil.com javascript then executes this loop
  - for (lots) do {...}
- All executions are allowed
  - Don't want to get terminated
- But this also trains the branch predictor
  - So the processor will attempt to run the loop one *more* time
  - This last time does computation on memory evil.com is not supposed to see
    - EG victim.com's cookies
  - Then checks how long it took which tells some bits about what was being read
    - Lather, rinse, repeat



# Countering Spectre: EAT RAM! NOM NOM NOM

- Chrome & Firefox now runs every origin as its own process: "Site Isolation"
  - Which means process level isolation from the operating system
- Defeats spectre-type attacks •
  - Now you can't even attempt to speculate across processes... since they have different page-tables they would load different data
    - If you could read across this barrier you've broken OS level isolation •
  - No such thing as a "Lightweight" isolation barrier
- But OS processes are expensive
  - Lots of memory overhead
  - Context-switching between processes is expensive: wipes out most processor state



# **Cookies & Web Authentication**

## Computer Science

- who have authenticated
- E.g., once browser fetched with logged-in user's info
  - An "authenticator"
- authenticated as Alice earlier"
  - Alice! Cookie thief!

## One very widespread use of cookies is for web sites to track users

## http://mybank.com/login.html?user=alice&pass=bigsecret with a correct password, server associates value of "session" cookie

Now server subsequently can tell: "I'm talking to same browser that

An attacker who can get a copy of Alice's cookie can access the server *impersonating* 







# Cross-Site Request Forgery (CSRF) (aka XSRF)

Computer Science 161 Fall 2020

- A way of taking advantage of a web server's cookie-based authentication to do an action as the user
  - Remember, an origin is allowed to fetch things from other origins
    - Just with very limited information about what is done...
  - E.g. have some javascript add an IMG to the DOM that is: https://www.exifltratedataplease.com/?{datatoexfiltrate} that returns a 1x1 transparent GIF
    - Basically a nearly unlimited bandwidth channel for exfiltrating data to something outside the current origin
    - Google Analytics uses this method to record information about visitors to any site using



Weaver

	Rank	Score	ID	
161 Fall	[1]	93.8	<u>CWE-89</u>	Improper Neutraliza ('SQL Injection')
	[2]	83.3	<u>CWE-78</u>	Improper Neutraliza ('OS Command Inje
	[3]	79.0	CWE-120	Buffer Copy without
	[4]	77.7	<u>CWE-79</u>	Improper Neutraliza ('Cross-site Scriptin
	[5]	76.9	CWE-306	Missing Authenticat
	[6]	76.8	<u>CWE-862</u>	Missing Authorization
	[7]	75.0	<u>CWE-798</u>	Use of Hard-coded
	[8]	75.0	<u>CWE-311</u>	Missing Encryption
	[9]	74.0	<u>CWE-434</u>	Unrestricted Upload
	[10]	73.8	<u>CWE-807</u>	Reliance on Untrust
	[11]	73.1	<u>CWE-250</u>	Execution with Unn
	[12]	70.1	<u>CWE-352</u>	Cross-Site Request
	[13]	69.3	<u>CWE-22</u>	Improper Limitation Traversal')
	[14]	68.5	<u>CWE-494</u>	Download of Code \
	[15]	67.8	<u>CWE-863</u>	Incorrect Authoriza
	[16]	66.0	<u>CWE-829</u>	Inclusion of Functio

## **Computer Science 161 Fall**

## Name ation of Special Elements used in an SQL Command ation of Special Elements used in an OS Command ection') t Checking Size of Input ('Classic Buffer Overflow') ation of Input During Web Page Generation ۱g') ion for Critical Function on Credentials of Sensitive Data of File with Dangerous Type ted Inputs in a Security Decision ecessary Privileges Forgery (CSRF) n of a Pathname to a Restricted Directory ('Path

Without Integrity Check

tion

onality from Untrusted Control Sphere



# Static Web Content

**Computer Science 161 Fall 2020** 

## <HTML> <HEAD> <TITLE>Test Page</TITLE> </HEAD> <BODY> <H1>Test Page</H1> <P> This is a test!</P>

</BODY> HTML>

## Visiting this boring web page will just display a bit of content.



Computer Science 161 Fall 2020

<HTML> <HEAD> <TITLE>Test Page</TITLE> </HEAD> <BODY> <H1>Test Page</H1> <P>> This is a test!</P> <IMG SRC="http://anywhere.com/logo.jpg"> </BODY> HTML>

## Visiting this page will cause our browser to automatically fetch the given URL.



## Computer Science 161 Fall 2020

<HTML> <HEAD> <TITLE>Evil!</TITLE> </HEAD> <BODY> <P>> This is a test!</P> </BODY> HTML>



So if we visit a page under an attacker's control, they can have us visit other URLs







Computer Science 161 Fall 2020

<HTML> <HEAD> <TITLE>Evil!</TITLE> </HEAD> <BODY> <P>> This is a test!</P> </BODY> </HTML>





# Web Accesses w/ Side Effects

## Computer Science 161

- Take a banking URL:
  - http://mybank.com/moneyxfer.cgi?account=alice&amt=50&to=bob
- So what happens if we visit evilsite.com, which includes:
  - <img width="1" height="1" src="http://mybank.com/</pre> moneyxfer.cgi?Account=alice&amt=500000&to=DrEvil">
  - Our browser issues the request ... To get what will render as a 1x1 pixel block
  - ... and dutifully includes authentication cookie!
- Cross-Site Request Forgery (CSRF) attack Web server *happily accepts the cookie*



# **CSRF** Scenario

**Computer Science 161 Fall 2020** 



## Server Victim mybank.com



5 Bank acts on request, since it has valid cookie for user

## Attack Server attacker.com





**Computer Science 161 Fall 2020** 

## URL fetch for posting a squig

GET &squig=squigs+speak+a+deep+truth COOKIE: session id=5321506

## Authenticated with cookie that browser automatically sends along



# do squig?redirect=%2Fuserpage%3Fuser%3Ddilbert

Web action with *predictable structure* 



# CSRF and the Internet of Shit...

## Computer Science

- Stupid IoT device has a default password
  - http://10.0.1.1/login?user=admin&password=admin
  - Sets the session cookie for future requests to authenticate the user
- Stupid IoT device also has remote commands
  - http://10.0.1.1/set-dns-server?server=8.8.8.8
  - Changes state in a way beneficial to the attacks
- Stupid IoT device doesn't implement CSRF defenses...
  - Attackers can do mass malvertized drive-by attacks: Publish a JavaScript advertisement that does these two requests



# CSRF and Malvertizing...

Computer Science 161

- You have some evil JavaScript:
  - http://www.eviljavascript.com/pwnitall.js
- This JavaScript does the following:
  - Opens a 1x1 frame pointing to http://www.eviljavascript.com/frame
- The frame then...
  - Opens a gazillion different internal frames all to launch candidate xsrf attacks!
- Then get it to run by just paying for it!
- Or hacking sites to include <script src="http://...">



